

## Network PTZ Controller

**Model: N1117-KBC**



### Features:

- Keyboard to Control:
  - Standalone DVR High Speed Dome
  - Network High Speed Dome Central Management Platform Network Video Server
- RS232, RS485 & Network Connections
- Three-Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips

## Specification:

<b>Operational</b>	
On Screen Display	English
LCD	Display command menu, protocol, current camera ID, output display ID and joys tick status
Max Dome Connection	Available to connect with 32pcs High Speed Dome
Protocol	Built-in multi-protocol such as Pelco_P, Pelco_D, VIDO_B02, Pelco matrix and so on; Baud rate can be selected
Electrify	Auto-test the baud rate, protocol and object dome and object monitor
Dom e lens control	Zoom , Focus and Iris Control
Dom e function operation	Preset/Scan/Pattern/Tour Setup
Communication interface	RS485,RS422,RJ45
RS485/RS422	DVR, PTZ Dome
RJ45	Matrix Connection
Matrix	Support PELCO Matrix
Keyboards linkage	DVR, PTZ dome, network PTZ dome, network video server
Communication frequency	2400,4800,960019200Bps
Communication distance	1.2km (RS485 and Rs 422can achieve it)
Baud Rate	2400
<b>Electrical</b>	
Input Voltage	12V DC
Input Range	9-12V AC/DC
Surge Suppression	1.5 KW transient
Power Consumption	1.5A
<b>Mechanical</b>	
Dimensions	320mmx190mmx50mm (WxD×H) (height: 100mm including joystick)
Weight	2.5KG
Construction	Plastic
<b>Environmental</b>	
Temperature	Operating: -0℃ to 50 ℃ Storage: -20 ℃ to 50 ℃
Relative Humidity	0% to 85%, non-condensing
<b>Regulatory</b>	
Emissions	FCC: Part 15, Class B CE: EN 55013
Immunity	CE: EN50130-4
Safety	EU: 73/23/EEC LVD

Note: Design & Specification are subject to change without prior notice.

